

Earth Ground Resistance Tester

Includes all hardware necessary to measure earth ground in 3 ranges to 2000 Ω

Features :

- 3-1/2 Digit (1999 count) multi-function LCD with Data Hold
- Measure Earth Resistance in Three ranges (20/200/2000 Ω)
- 2mA (800Hz) Test Current and Frequency
- 0 to 200VAC (40 to 500Hz) AC Earth Voltage/Frequency
- $\pm 1.0\%$ of reading basic accuracy
- Auto Power Off and 3 minute Timer
- Overload Protection
- Open circuit, overrange, and low battery indications
- Meets IEC-1010 (Cat. III - 600V)
- Complete with test leads, auxiliary earth bars, heavy duty case, six 1.5V AA batteries



Specifications

Earth Ground Resistance ranges:	20 / 200 / 2000 Ω
Resolution:	0.01 Ω / 0.1 Ω / 1 Ω
Test Current / Frequency:	2mA (800Hz)
AC Earth Voltage / Frequency:	0-200VAC (40 to 500Hz)
Basic Accuracy:	$\pm 1\%$ reading + 2 digits
Dimensions/Weight:	6.4x3.9x2" (163x100x50mm) / 25.7oz. (800g)

382152 Digital Earth Ground Resistance Tester

382153 Replacement Earth Bars (2 pk)

EASTCO LIMITED 儀 高 儀 器 有 限 公 司



香港總公司
香港新界荃灣沙咀道26-38號
匯力工業中心2字樓26室
電話: (852)2456 1823
傳真: (852)2469 1767
電郵: info@eastco-hk.com
網址: <http://www.eastco-hk.com>
網絡實名: 儀高南儀器

中國公司
儀高南儀器(深圳)有限公司
中國深圳市八卦四路素泰克大廈
3樓V區 郵編: 518029
電話: (86-755) 8241 3890
傳真: (86-755) 8241 3857
電郵: shenzhen@eastco-hk.com

上海辦事處
中國上海市滬太路701號
18樓1810室
郵編: 200072
電話: (86-21) 5653 6311
傳真: (86-21) 5653 6309
電郵: shanghai@eastco-hk.com